

STAINLESS STEEL


For fixing long-life panels to steel or aluminium, where high levels of corrosion exist.

TYPE 17 (GRADE 304) with 16mm Aluminium Bonded Washer




d	Length	T	F1	F2	Order No	Pack Qty
Guage	Length	Metal Thickness	Fix to Timber	Fix to Steel		
14-10	25	1.2	1.2		6-037-0022-4	500
	50	1.2	18		6-037-0023-2	1000
	65	1.2	33		6-037-0024-1	1000
	75	1.2	43		6-037-0025-9	500
	90	1.2	58		6-037-0026-7	500

TEK (GRADE 304)



d	Length	T	F1	F2	Order No	Pack Qty
12-11	25	4.5		9	6-312-0009-6	1000
14-14	52	4.5		39	6-392-0008-8	
14-14	80	4.5		45	6-392-0010-1	
14-14	90	4.5		71	6-392-0011-2	

TAPTITES (GRADE 304) Hex Head with 16mm Aluminium Bonded Washer



d	Length	Order No	Pack Qty
14-24	25	6-237-0023-2	500
14-24	65	6-237-0026-4	500
14-24	75	6-237-0027-2	500

1. Measure the total thickness of the materials to be fastened.
2. Choose a TAPTITE long enough to allow at least three threads to protrude beyond the steel being fastened to.
3. Drill a pilot hole through the materials to be joined.

Recommended hole sizes:

Material	Hole Size
3mm Aluminium	5.3mm
6mm H.R.S	5.6mm
12mm H.R.S	5.7mm
1.2 - 2.4 mm G450	5.5mm

4. Select a 5/16" Hex Socket.
5. Install TAPTITE with a power screwdriver set to a speed no more than 300rpm.

STAINLESS STEEL SUNDRY SCREWS



Pan Head

8	25	8x40-PAN-316	1000
---	----	--------------	------



Bugle Head

8	40	8x40-BGL-316	1000
8	50	8x50-BGL-316	1000



Rib Head

9	40	9x40-RIB-316	1000
9	50	9x50-RIB-316	500



Countersunk Head

10	40	10x40-SS-AB	1000
10	50	10x50-SS-AB	500