

Product Name : PERFORMANCE CLEAR**Other Names** : None**Part No.** : PERFCLG310**MSDS No.** : NZ3100**Date & Issue** : NOV 3/ ISSUE A

Ramset NZ

A Division of ITW NZ Ltd

PO Box 40-031

Glenfield, Auckland

www.ramset.co.nz

1: RECOMMENDED USE

Multipurpose paintable, elastomeric flexible Sealant

2: HAZARDS IDENTIFICATION

UN No : 1133

Hazard Class :

Subsidiary Risk :

SPEC EPG :

NIOSH :

D G Class : 3

Hazchem Code : 3 [Y]

Poisons Schedule : 5

CAS No :

G T EPG :

Packing Group : III

IMDG :

3: PHYSICAL DESCRIPTION & PROPERTIES

Appearance : Transparent paste

Specific Gravity : 0.94 g/mL

Form : Semi-solid

Vapor Pressure : 13.00 millibar

Solubility in Water : Insoluble

Flammability Ltd : Ignition point – 370.0 deg C

Boiling Point :

Melting Point :

Flashpoint : 25 deg C

Other :

4: COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name, (CAS No) Content Proportion

: N-Butyl acetate : 123-86-4 :

Contents : **H**igh >60% **M**edium 10 – 60% **L**ow 1 – 10% **V**ery Low <1%**PRINT DOCUMENT****BACK TO CONTENTS**

NATIONAL POISONS INFORMATION CENTRE

RAMSET NZ

MSDS's AVAILABLE ON LINE AT

PAGE No

: 0800 764 766

: 09 444 3510

: www.ramset.co.nz

: 1 of 4

Product Name :PERFORMANCE CLEAR**Other Names** :None**Part No.** :PERFCLG310**MSDS No.** :NZ3100**Date & Issue** :NOV 3/ ISSUE A

Ramset NZ

A Division of ITW NZ Ltd

PO Box 40-031

Glenfield. Auckland

www.ramset.co.nz**5: HEALTH HAZARD INFORMATION******TAKE A COPY OF THIS MSDS TO THE DOCTOR******HEALTH EFFECTS: ACUTE:**Eyes

May be irritating in contact with eye.

Skin

The product is not considered to be a skin irritant.

Inhaled

Vapour may be irritating to the respiratory tract.

Swallowed

Harmful if swallowed.

HEALTH EFFECTS: CHRONIC:

Non-sensitising.

FIRST AID****Take a copy of this MSDS to the Doctor****Eyes

Rinse thoroughly with plenty of water and seek medical advice.

Skin

In case of contact with skin wash off immediately with soap and water. If rash occurs and persists seek medical advice.

Inhaled

Ensure supply of fresh air. In the event of symptoms refer to medical treatment.

Swallowed

If swallowed, DO NOT induce vomiting. Give a glass of water to drink and seek medical advice.

Advice to Doctor

Treat symptomatically.

First Aid facilities

Ensure that eyewash stations are easily accessible.

Toxicity data**PRINT DOCUMENT****BACK TO CONTENTS**

NATIONAL POISONS INFORMATION CENTRE

RAMSET NZ

MSDS's AVAILABLE ON LINE AT

PAGE No

: 0800 764 766

: 09 444 3510

: www.ramset.co.nz

: 2 of 4

Product Name :PERFORMANCE CLEAR**Other Names** :None**Part No.** :PERFCLG310**MSDS No.** :NZ3100**Date & Issue** :NOV 3/ ISSUE A

Ramset NZ

A Division of ITW NZ Ltd

PO Box 40-031

Glenfield. Auckland

www.ramset.co.nz**6: PRECAUTIONS FOR USE****EXPOSURE LIMITS:**

Ingredient	TLV/TWA	TLV/STEL
N-Butyl acetate	950 mg / m ³	950 mg / m ³

VENTILATION:

Dilution ventilation to ensure airborne levels are kept below the exposure limits.

PERSONAL PROTECTION:Eyes

Safety glasses.

Hands & Feet

Nitrile gloves. Wash hands before breaks and after work.

Respiratory

Dilution ventilation is normally adequate. However, where concentrations in air may exceed the exposure limits, or where an individual is sensitive to the airborne component, wear respirator complying with AS1716.

Other**FLAMMABILITY:**

Flammable.

ENVIRONMENT:**OTHER PRECAUTIONS:**[PRINT DOCUMENT](#)[BACK TO CONTENTS](#)

Product Name :PERFORMANCE CLEAR**Other Names** :None**Part No.** :PERFCLG310**MSDS No.** :NZ3100**Date & Issue** :NOV 3/ ISSUE A

Ramset NZ

A Division of ITW NZ Ltd

PO Box 40-031

Glenfield, Auckland

www.ramset.co.nz**7: SAFE HANDLING & STORAGE****STORAGE & TRANSPORT:**

Store in a cool dry place out of direct sunlight. Keep away from sources of ignition. Class 3 Flammable. Do not smoke. Take precautionary measures against static discharges. Storing temperature max: 60 deg C.

PACKAGING & LABELLING:**SPILLS & DISPOSALS:**

Use personal protective clothing. Do not discharge into the drains/surface waters/groundwater. Remove all ignition sources. Contain and absorb small quantities with sand or vermiculite. Wipe up and collect residues in flammable waste container (polyethylene). For disposal contact state Land Waste Management Authority.

OTHER PRECAUTIONS:**8: FLAMMABILITY**

Fire/Explosion hazard : Hazchem 3[Y]E.

Upper Explosion Limit : 10.4

Dust Explosion Limit :

Lower Explosion Limit : 3.0

May Decompose Explosively :

Extinguishing Media : Foam, dry powder and carbon dioxide or water spray jet. Do not use full water jet.

Other : Fire-fighting personnel to wear self-contained breathing apparatus.

HAZARDOUS DECOMPOSITION PRODUCTS:

Carbon monoxide, carbon dioxide and other oxides of carbon.

9: OTHER INFORMATION

None

[PRINT DOCUMENT](#)[BACK TO CONTENTS](#)

NATIONAL POISONS INFORMATION CENTRE

RAMSET NZ

MSDS's AVAILABLE ON LINE AT

PAGE No

: 0800 764 766

: 09 444 3510

: www.ramset.co.nz

: 4 of 4