

Product Name : Gyp-Fast Wallboard Adhesive**Other Names** : **None****Part No.** : GFSAU600**MSDS No.** : NZ6400**Date & Issue** : Jan 05 Issue A

Ramset NZ

A Division of ITW NZ Ltd

PO Box 40-031

Glenfield. Auckland

www.ramset.co.nz

1: RECOMMENDED USE

Gyp-Fast Wallboard Adhesive is a general purpose solvent based wallboard adhesive

2: HAZARDS IDENTIFICATION

UN No	: 1133	Hazchem Code	: 3[Y]E
Hazard Class	:	Poisons Schedule	:
Subsidiary Risk	:	CAS No	:
SPEC EPG	:	G T EPG	:
NIOSH	:	Packing Group	: III
NZ D G Class	: 3	IMDG	:
Other	:	Other	:

3: PHYSICAL DESCRIPTION & PROPERTIES

% Volatile by Weight	: 59.0 approx	Appearance	: Pale yellow thixotropic paste
Specific Gravity	: 1.01	Boiling Point	: 50 to 114
Vapor Density	: 3.2 (Air = 1)	Odour	: Solvent Odour
Vapor Pressure	: 70mm HG	Flashpoint	: <-20 Degrees C
Solubility in Water	: 0.0%	Evaporation rate	: 2.8 (Butyl Acetate = 1)

4: COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Names	CAS No	Content	WES-TWA	WES-STEL
: Hydrocarbon Mixture	: 64742-89-8	: Low	: 400 ppm	:-
: Toluene (Methyl Benzene)	: 108-88-3	: Low	: 50 ppm	:-

Contents : **H**igh >60% **M**edium 10 – 60% **L**ow 1 – 10% **V**ery Low <1%**PRINT DOCUMENT****BACK TO CONTENTS****NATIONAL POISONS INFORMATION CENTRE**
RAMSET NZ
MSDS's AVAILABLE ON LINE AT
PAGE No: 0800 764 766
: 09 444 3510
: www.ramset.co.nz
: 1 of 4

Product Name : Gyp-Fast Wallboard Adhesive**Other Names** : **None****Part No.** : GFSAU600**MSDS No.** : NZ6400**Date & Issue** : Jan 05 Issue A

Ramset NZ

A Division of ITW NZ Ltd

PO Box 40-031

Glenfield, Auckland

www.ramset.co.nz**5: HEALTH HAZARD INFORMATION******TAKE A COPY OF THIS MSDS TO THE DOCTOR******HEALTH EFFECTS: ACUTE:**Eyes

Causes eye irritation and pains

Skin

May cause skin irritation

Inhaled

hazardous if inhaled

Swallowed

No hazard know at this time

Other**FIRST AID**Eyes

Immediately wash out with running water for at least 15 minutes. Seak medical treatment

Skin

Immediately wash off with soapy water Seak medical treatment

Inhaled

Rest in freash air and seak medical treatment. If not breathing give artificial respiration. If breathing difficult give oxygen. Call doctor

Swallowed

Do not induce vomiting. If conscious give 1-2 glasses of water. Call doctor

Advice to Doctor

Treat symptomatically

Toxicity data**SYMPTOMS OF OVEREXPOSURE**

Irritation, dizziness, Giddiness, Weakness, Headache, Nausea, Diarrhoea, Vomiting

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE

None know to Ramset

ENTRY ROUTE

Contact, inhalation

CHRONIC EFFECTS

Long term over exposure to the hazardous materials in this product have been assisiated with dermatitis, kidney and liver damage

TARGET ORGANS

Central nervous system, kidneys, liver, skin

PRINT DOCUMENT**BACK TO CONTENTS****NATIONAL POISONS INFORMATION CENTRE****RAMSET NZ****MSDS's AVAILABLE ON LINE AT****PAGE No****: 0800 764 766****: 09 444 3510****: www.ramset.co.nz****: 2 of 4**

Product Name : Gyp-Fast Wallboard Adhesive
Other Names : **None**
Part No. : GFSAU600
MSDS No. : NZ6400
Date & Issue : Jan 05 Issue A

Ramset NZ
A Division of ITW NZ Ltd
PO Box 40-031
Glenfield, Auckland
www.ramset.co.nz

6: PRECAUTIONS FOR USE

EXPOSURE LIMITS:

VENTALATION:

Use in a well ventilated area. Local exhaust is preferred to keep vapors /particles below TWA value. Mechanical area wide ventilation is acceptable

PERSONAL PROTECTION:

Eyes

Wear safety glasses

Hands & Feet

Wear Neoprene gloves

7: SAFE HANDLING & STORAGE

STORAGE & TRANSPORT:

Store in a cool (15-25 Degrees C) dark and dry place for maximum shelf life. Keep tightly closed

PACKAGING & LABELLING:

SPILLS & DISPOSALS:

Warning EXTREMELY FLAMMABLE

Evacuate people on the leadward side of contaminated area. Remove any sources on ignition. Use protective clothing when cleaning. Package product in steel drums which are in good condition.

Dispose of in accordance with local rules. Be aware that local requirements may differ widely depending on the location and may in many cases be different from national rules. When intending to dispose of this material, the user is advised that this product may be classified as Harzardous Waste under regulations in effect at the time that this MSDS was created

OTHER PRECAUTIONS:

Avoid Strong Oxidisers and acids

[PRINT DOCUMENT](#)

[BACK TO CONTENTS](#)

NATIONAL POISONS INFORMATION CENTRE
RAMSET NZ
MSDS's AVAILABLE ON LINE AT
PAGE No

: 0800 764 766
: 09 444 3510
: www.ramset.co.nz
: 3 of 4

Product Name : Gyp-Fast Wallboard Adhesive**Other Names** : **None****Part No.** : GFSAU600**MSDS No.** : NZ6400**Date & Issue** : Jan 05 Issue A

Ramset NZ

A Division of ITW NZ Ltd

PO Box 40-031

Glenfield. Auckland

www.ramset.co.nz

8: FLAMABILITY

Fire/Explosion hazard	:	Upper Explosion Limit	: 7.24 % (Calculated)
Extinguishing Media	:	Lower Explosion Limit	: 1.18 % (Calculated)
May Decompose Explosively	:	Auto Ignition Temp	:

Extinguishing Media

water spray, foam powder, dry chemical, carbon dioxide

Other

Remove sources of ignition. Extinguish the fire using fire fighting media listed above. Cool surroundings by spraying with water to prevent the fire from spreading. Use suitable respiratory devices.

HAZARDOUS POLYMERIZATION WILL NOT OCCUR:

Unknown due to the complex nature of this material. Fumes from complete or incomplete combustion of this material may include carbon monoxide, carbon dioxide, water vapor oxides of nitrogen or a wide variety of innocuous or toxic fumes. Hydrogen Chloride may be produced .

9: OTHER INFORMATION

None

[PRINT DOCUMENT](#)[BACK TO CONTENTS](#)

NATIONAL POISONS INFORMATION CENTRE

RAMSET NZ

MSDS's AVAILABLE ON LINE AT

PAGE No

: 0800 764 766

: 09 444 3510

: www.ramset.co.nz

: 4 of 4