



**Product description**

GAP SEAL is flexible to resist cracking when used to seal gaps and cracks prior to painting.

GAP SEAL is paintable with acrylic and oil based surface coatings.

**Recommended uses**

- Sealing gaps and cracks in and around:
  - Window frames
  - Architraves
  - Skirting boards
  - Picture and chair rails.
- Sealing around vanities and baths
- Internal corners of walls
- Sealing cracks, joints and gaps where rigid fillers crack or fall out

**Suitable for use on**

- Plasterboard
- MDF
- Plywood
- Ceramic tiles
- Laminated plastics
- Stainless steel
- Aluminium
- Timber
- Fibre cement
- Concrete
- Brick

**Features and benefits**

- Resists cracking - flexible
- Paintable
- User friendly - clean up with water
- User friendly - low odour
- Easy to use - sag resistant

**Precautions**

- Not to be used for applications where prolonged contact with or immersion in water are expected
- Apply to substrates with temperature above 5°C
- Sealant may not dry when used in totally confined or air free spaces
- Pre-testing sealant with marble, limestone or granite for staining and/or discoloration recommended
- Do not apply to any material containing bitumen
- Not for glazing applications
- Do not use in expansion and other dynamic joints
- Do not use to fill gaps between tongue-in-groove boards or weather boards

**Typical Properties**

Property	Typical Value
Chemical type	Water-based acrylic
Service temperature	-10°C to +80°C
Application temperature	+5°C to +35°C
Tool working time	15 mins at 20°C
Max. joint movement	±5%
Max. joint width	50mm
Elongation at break	400% ASTM D412
Cure rate	2mm per 24 hour period
Cure hardness	Shore D50
Skinning time	30 mins at 20°C
Paintable	Acrylic and vinyl paints - 30 mins at 20°C. Oil based paints - 24 hours

**Tooling Time**

Complete tooling and finishing within 30 minutes of application @ 20°C.

**Painting**

Water based paints (Acrylic or vinyl paint) after 30 minutes @ 20°C. Oil or solvent based paints after 24 hours.

**Clean Up**

Clean up uncured material and equipment within 15 minutes (@ 20°C) with tap water. Remove dried Gap Seal by sanding or scraping.

**Colours, Pack Sizes and Order Numbers**

Colour	Pack Size	Order Number
White	300ml cartridge	GPSLWHG450

**Storage**

Store between 5°C and 30°C. Shelf life is 2 years in original unopened container.

**Health and Safety**

Avoid contact with the skin, eyes and avoid breathing vapour. For more detailed information refer to the Material Safety Data Sheet. Call 0800 726 738 or visit the website [www.ramset.co.nz](http://www.ramset.co.nz)