



Product description

Ramset Performance Clear is a one component non-sag elastomer sealant. It works equally well in wet or dry conditions and seals through water and oil film to stop leaks and provide fast, flexible seals. It can be used in rain, standing water or in oily conditions and exhibits extraordinary adhesion strength. It can be painted over.

Recommended uses

- Suitable for all roofing applications.
- Suitable for wet or dry conditions.
- Seals joints subject to exposure of moisture.
- May be painted with conventional applicable paints.

Suitable for use on

- Sheet metal
- Zinc
- Steel
- Copper
- Bitumen
- Glass
- Wood
- Stone
- Asphalt
- Ceramics
- Concrete
- Plaster
- Brickwork
- Marble

Features and benefits

- One part
- Non sag
- Multi-purpose with exceptional adhesion and flexural properties.

Precautions

- For joint depth exceeding 6mm, Ramset backer rod should be used.
- Some paints may crack in high joint movement situations.
- Consult paint specifications.
- Not recommended for traffic bearing surfaces.
- Not recommended for use where food is processed or stored unless sealant is cured for two weeks at room temperature (due to solvent release).
- Not suitable for aquarium or plastic (perspex) materials.

Typical Properties

Property	Typical Value
Appearance	Clear non-sag thixotropic paste
Satin and colour changes	None visible
Chemical type	Synthetic polymer blend
Service temperature	-25°C to +100°C
Application Temperature	+5°C to +50°C
Tool working time	Approx. 15mins at 20°C
Max. joint movement	+25% / -25%
Max. joint width	20mm

Cure

Full cure, 3 to 7 days. Paintable 24 hours.

Clean up

Tools, equipment and uncured Performance may be cleaned up with Ramset solvent.

Colours, Pack Sizes and Order Numbers

Colour	Pack Size	Order Number
Clear	310g	PERFCLG310

Storage

Store between 5°C and 25°C. Shelf life is 1 year in original unopened container.

Health and Safety

Avoid contact with the skin, eyes and avoid breathing vapour. For more detailed information refer to the Material Safety Data Sheet. Call 0800 726 738 or visit the website www.ramset.co.nz